

# Goldsmiths Research Online

*Goldsmiths Research Online (GRO)  
is the institutional research repository for  
Goldsmiths, University of London*

## Citation

Henningsen, Malte; Garagnani, Max and Pulvermüller, Friedemann. 2020. 'Influence of verbal labels on concept formation and perception in a deep unsupervised neural network model'. In: 14th International Conference of Cognitive Neuroscience. Helsinki, Finland 3 - 7 June 2020. [Conference or Workshop Item] (Forthcoming)

## Persistent URL

<http://research.gold.ac.uk/28224/>

## Versions

The version presented here may differ from the published, performed or presented work. Please go to the persistent GRO record above for more information.

If you believe that any material held in the repository infringes copyright law, please contact the Repository Team at Goldsmiths, University of London via the following email address: [gro@gold.ac.uk](mailto:gro@gold.ac.uk).

The item will be removed from the repository while any claim is being investigated. For more information, please contact the GRO team: [gro@gold.ac.uk](mailto:gro@gold.ac.uk)

# **Influence of verbal labels on concept formation and perception in a deep unsupervised neural network model**

## **OBJECTIVES/RESEARCH QUESTION**

Whether language influences perception and thought remains a subject of intense debate. Would the presence or absence of a linguistic label facilitate or hinder the acquisition of new concepts? We here address this question in a neurocomputational model.

## **METHODS**

We used a computational brain model of fronto-occipital (extrasyllvian) and fronto-temporal (perisyllvian) cortex including spiking neurons. With Hebbian learning, the network was trained to associate word forms (phonological patterns, or “labels”) in perisyllvian areas with semantic grounding information (sensory-motor patterns, or “percepts”) in extrasyllvian areas. To study the effects of labels on the network’s ability to spontaneously develop distinct semantic representations from the multiple perceptual instances of a concept, we modelled each to-be-learned concept as a triplet of partly overlapping percepts and trained the model under two conditions: each instance of a perceptual triplet (patterns in extrasyllvian areas) was repeatedly paired with patterns in perisyllvian areas consisting of either (1) a corresponding word form (label condition), or (2) white noise (no-label condition).

To quantify the emergence of neuronal representations for the conceptually-related percepts, we measured the dissimilarity (Euclidean distance) of neuronal activation vectors during perceptual stimulation. Category learning performance was measured as the difference between within- and between-concept dissimilarity values (DissimDiff) of perceptual activation patterns.

## **RESULTS**

The presence or absence of a linguistic label had a significant main effect on category learning ( $F=2476$ ,  $p<0.0001$ , DissimDiff with labels  $m=0.92$ ,  $SD=0.32$ ; no-labels  $m=0.36$ ,  $SD=0.21$ ). DissimDiff values were also significantly larger in areas most important for semantic processing, so-called semantic-hubs, than in sensorimotor areas (main effect of centrality,  $F=2535$ ,  $p<0.0001$ ). Finally, a significant interaction between centrality and label type ( $F=711$ ,  $p<0.0001$ ) revealed that the label-related learning advantage was most pronounced in semantic hubs.

## **CONCLUSION**

These results suggest that providing a referential verbal label during the acquisition of a new concept significantly improves the cortex’ ability to develop distinct semantic-category representations from partly-overlapping (and non-overlapping) perceptual instances. Crucially, this effect is most pronounced in higher-order semantic-hub areas of the network. In sum, our results provide the first neurocomputational evidence for a “Whorfian” effect of language on perception and concept formation.